

SIOBLAST BX

SETUP GUIDE

FRONT SUSPENSION

Shock position

1 2 3

Upper arm position

1 2

Caster angle
Standard: 10°
Option: 4°

Front shock
Oil: _____
Pistons: _____
Spacer: _____
Springs: _____

Sway bar
Diameter: _____ mm

1mm

Toe angle

Front toe angle _____
Notes _____

Rear toe angle _____
Notes _____

1 2

Camber angle

Camber front _____
Notes _____

Camber rear _____
Notes _____

Rideheight front _____
Rideheight rear _____

REAR SUSPENSION

Shock position

1 2 3

Upper arm position

1 2

Wheelbase adjustment

Rear _____ mm

Front _____ mm

1 2

1 2

1 2 3

Rear shock
Oil: _____
Pistons: _____
Spacer: _____
Springs: _____

Sway bar
Diameter: _____ mm

1mm

Tire

Front _____ Rear _____

Type: _____ Type: _____

Foam: _____ Foam: _____

Motor: _____ Battery: _____

Spur Gear: _____ ESC: _____

Pinion Gear: _____ Servo: _____

Track conditions

Size: Open Med Tight

Traction: High Med Low

Surface: Smooth Med Bumpy

Diff Oil

Front: _____

Rear: _____

Comment

Name: _____

Date: _____

Track: _____