

FLOW X OFFROAD - V3.1 / V3.2

Driver:					Motor:		Rotor:	mm
Date:					Timing:	°	Gearing:	
Event:					Battery:		Charged to:	V
Track:					Fan:	ESC	Motor	
Racing Class:					ESC Temp.:	blinks	Motor Temp.:	blinks
Size:	Small	Medium	Large	Extra Large	Air Temp.:	Track Temp.:		
Surface:	Dirt	Carpet	Astroturf	Asphalt	Car:			
Traction:	Low	Medium	High	Very High	Radio:			
Moisture:	Dry	Damp	Wet		EPA:	% Throttle	% Brake	
Condition:	Indoor	Outdoor	Dusty	Hard Packed	EXPO:	% Throttle	% Brake	
	Bumpy	Grooved	Smooth	Loamy				

MODE		LED	0	1	2	3	4	5	6	7	8	9	10	
1	Brake	Auto Brake (%)	0	3	6	9	12	15	18	21	24	27	30	
		Brake Type	-	SEMI X			X			BR2		BDX-0		
		Brake Ramp (%)	-	70	85	SP	70	85	SP	70	SP	70	SP	
3		Initial Brake (%)	S	0	1	2	3	4	5	7	9	12	15	20
4	Throttle	Initial Drive (%)		-	1	2	3	4	5	6	7	8	9	10
5		Torque Feel		0	1	2	3	4	5	-				
6		Timing (°)		0	3	6	9	12	15	18	21	24	27	30
7		Ramp (°/10kRpm)		1	1,5	2	2,5	3	3,5	4	4,5	5	7,5	10
8		Delay (kRpm)		F	F	5	7,5	10	12,5	15	17,5	-		
9	Protection			ALL	ESC	NONE	-							

no value / hidden mode

Factory default settings

F LED blinking fast

S LED blinking slow

Value Summary:

NOTES