

FLOW X OFFROAD - V3.1 / V3.2

Driver:					Motor:	Rotor:	mm		
Date:					Timing:	°	Gearing:		
Event:					Battery:	Charged to: V			
Track:					Fan:	ESC	Motor		
Racing Class:					Qualify:	Finish:	ESC Temp.: blinks Motor Temp.: blinks		
Size:	Small	Medium	Large	Extra Large	Air Temp.:		Track Temp.:		
Surface:	Dirt	Carpet	Astroturf	Asphalt	Car:				
Traction:	Low	Medium	High	Very High	Radio:				
Moisture:	Dry	Damp	Wet	EPA:				% Throttle % Brake	
Condition:	Indoor	Outdoor	Dusty	Hard Packed	EXPO:				% Throttle % Brake
	Bumpy	Grooved	Smooth	Loamy					

MODE		LED	0	1	2	3	4	5	6	7	8	9	10
1	Brake	Auto Brake (%)											
		Brake Type	F										
		Brake Ramp (%)											
3		Initial Brake (%)	S										
4	Throttle	Initial Drive (%)											
		Torque Feel											
		Timing (°)											
		Ramp (°/10kRpm)											
		Delay (kRpm)		F	F								
9		Protection											

 no value / hidden mode
 Factory default settings
 F LED blinking fast
 S LED blinking slow

Value Summary:									
----------------	--	--	--	--	--	--	--	--	--

NOTES