

FLOW X OFFROAD - V3.1 / V3.2

Driver:					Motor:	Rotor:	mm		
Date:					Timing:	°	Gearing:		
Event:					Battery:	Charged to: V			
Track:					Fan:	ESC	Motor		
Racing Class:					Qualify:	Finish:	ESC Temp.: blinks Motor Temp.: blinks		
Size:	Small	Medium	Large	Extra Large	Air Temp.:	Track Temp.:			
Surface:	Dirt	Carpet	Astroturf	Asphalt	Car:				
Traction:	Low	Medium	High	Very High	Radio:				
Moisture:	Dry	Damp	Wet	EPA:				% Throttle % Brake	
Condition:	Indoor	Outdoor	Dusty	Hard Packed	EXPO:				% Throttle % Brake
	Bumpy	Grooved	Smooth	Loamy					

MODE		LED	0	1	2	3	4	5	6	7	8	9	10
1	Auto Brake (%)		0	3	6	9	12	15	18	21	24	27	30
2	Brake Type	F	-	SEMI X			X			BR2		BDX-0	
	Brake Ramp (%)			70	85	SP	70	85	SP	70	SP	70	SP
3	Initial Brake (%)	S	0	1	2	3	4	5	7	9	12	15	20
4	Initial Drive (%)		-	1	2	3	4	5	6	7	8	9	10
5	Torque Feel		0	1	2	3	4	5	-				
6	Timing (°)		0	3	6	9	12	15	18	21	24	27	30
7	Ramp (°/10kRpm)		1	1,5	2	2,5	3	3,5	4	4,5	5	7,5	10
8	Delay (kRpm)	F F	5	7,5	10	12,5	15	17,5	-				
9	Protection		ALL	ESC	NONE	-							

no value / hidden mode

Factory default settings

F LED blinking fast

S LED blinking slow

Value Summary:

NOTES