

# FLOW X STOCK SPEC - V5.1 / V5.2

Driver:	Motor:	Rotor:	mm			
Date:	Timing:	°	Gearing:			
Event:	Battery:	Charged to:	V			
Track:	Fan:	ESC	Motor			
Racing Class:	Qualify:	Finish:	ESC Temp.: blinks Motor Temp.: blinks			
Size:	Small	Medium	Large	Extra Large	Air Temp.:	Track Temp.:
Surface:	Dirt	Carpet	Astroturf	Asphalt	Car:	
Traction:	Low	Medium	High	Very High	Radio:	
Moisture:	Dry	Damp	Wet	EPA:	% Throttle	% Brake
Condition:	Indoor	Outdoor	Dusty	Hard Packed	EXPO:	% Throttle % Brake
	Bumpy	Grooved	Smooth	Loamy		

MODE		LED	0	1	2	3	4	5	6	7	8	9	10				
1	Brake	Auto Brake (%)	F			0	1	3	5	7	9	11	13	15	20	25	
		Brake Type	F			SEMI X	X-Stock	BD3	BDX-S	-							
		Initial Brake (%)	S			0	1	3	5	7	9	11	13	15	20	25	
4	Throttle	Initial Drive (%)															
		IDFC															
		Torque Feel															
		Timing (°)															
		Ramp (°/10kRpm)															
		Delay (kRpm)															
		Protection															

  no value / hidden mode     
   Factory default settings     
 F LED blinking fast      S LED blinking slow

Value Summary:

NOTES